



STANDARD GABION SIZES					
LETTER CODE	LENGTH	WIDTH	HEIGHT	NUMBER OF DIAPHRAGMS	VOLUME
					CY
А	6'-0"	3'-0"	3'-0"	1	2.0
В	9'-0"	3'-0"	3'-0"	2	3.0
С	12'-0"	3'-0"	3'-0"	3	4.0
D	6'-0"	3'-0"	1′-6"	1	1.0
E	9'-0"	3'-0"	1′-6"	2	1.5
F	12'-0"	3'-0"	1′-6"	3	2.0
G	6'-0"	3'-0"	1'-0"	1	0.66
н	9'-0"	3'-0"	1'-0"	2	1.0
I	12'-0"	3'-0"	1'-0"	3	1.33



98



NOTE:

NOTES:

- Internal connecting wire (13.5-gage) to be installed across width of interior Gabions and across width and length of end Gabions.
- 2. Internal connecting wire and Gabion mesh shall be galvanized.
- Internal connecting wires required on all gabions 3'-0" high.
- 4. Preformed stiffeners (11-gage or 9-gage) are an acceptable alternative to internal connecting wires. Install them as recommended by manufacturer or as directed by the Engineer at ½3 points.
- 5. Place rock in end Gabion cell first, and continue by filling interior Gabion cells.
- 6. For Gabion dimensions, refer to table "Standard Gabion Sizes".

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

GABION BASKET DETAILS No. 1

NO SCALE

D100A